


STREETSMART

Product Leaflet



User Interface

Touch technology Capacitive touch
Reinforced 6mm-thick tempered glass (IK10)
Intuitive UI

Display Graphical 9"7 colour screen
Resolution: 1024 (W) x 768 (H)
Light intensity: 552cd/m²
Automatic adaptive backlight.
Anti-reflective treatment

CPU system

Appl. & data Operating system : Android TM 5.1
Samsung Exynos 5422 based SOM
(chip of galaxy S4)
2Go of RAM

Communication

4G Supported in certified countries
LAN Supported (Mains only)
Type of data Transactions, Tariffs, Parameters,
Software, OS, Statistics, Alarms, Parking
rights...

Printer

Thermal graphic Horizontal/Vertical printing
Text & Logo
8 dots per mm per line
448 dots per column
Tickets Paper or self-adhesive tickets
Standard or Premium quality
(long life/severe exposure)
Tickets per roll: up to 6500
Size: 60 (W) x 70 (L) mm – (2.36" x 2.76")

Electrical data

Mains 230V
Solar 16.5W Top hat solar panel
Battery operation 2 batteries 27Ah & 42Ah
12V DC

Card payment

M1000 card reader PCI PTS 3.1 / 4.1, EMV Level 1
EMV Level 2, AFAS (France)
P1000 PINPad PCI PTS 3.1 / 4.1
A1000 Contact-less antenna PCI PTS 4.1
EMV contact-less Level 1
EMV contact-less Level 2 v2.5
(Entry point, C2/Visa, C3/MasterCard, C4/Amex)

Coin payment

Selector Patented motor-driven coin selector
14 different coins/ token accepted
Infrared/Magnetic detection technologies
Collection Exchangeable coinbox for Rapide collection:
Capacity: 4.6 liters – 2700 coins
Empty weight: 1.6kg – 3.53 lb
Coinbox for Transfer collection:
Capacity: 2600 coins
Transfer Canister:
Capacity: 5.8 liters

Environmental conditions

Operating temp. -25°C to + 55°C (-77°F to + 131°F)
guaranteed during 24 hours
Storage temp. -40°C to +70°C (-104°F to +158°F)
guaranteed during 16 hours
Relative humidity Up to 95% RH at 55°C (131°F)
Recyclability From 80% to 95% depending on options available (ISO 22628)
European directives – 2011/65 RoHS and 2012/19 WEEE

Security

Locks Mechanical and/or Electronic locking for upper and collection doors
Identification via maintenance card or electronic key
Enhancements Additional armourings
Multi-sensor attack detector:
Vibration and tilt detection
Reinforced locks

Miscellaneous

Climatic pack Protection of the coin and ticket bowls
Mounting frame Compatible with Flowbird and main competitors base anchoring
Anchoring Excavation with pedestal
Flat ground with/without pedestal
1D-2D QR code reader

Cabinet and Pedestal

Dimensions 1.714 x 475 x 383 mm
(HxWxD)
(with 16.5W solar module)
67.48" x 18.7" x 15.79"
(with 16.5W solar module)
Weight 90 kg – 198 lb
Battery 27Ah: 8.6 kg – 18.96 lb
Battery 42Ah: 13.8 kg – 30.42 lb
Construction Anti-corrosive & anti-graffiti coated steel
Compliance EN 12414
Safety: IP24D & IK9 to IK10
Coins storage: DTG07131
(EN14450 Level2)
ISO 9001 - ISO 14001 - ISO 18001

